

Fire Hose Reels

Fire hose reels provide an accessible and controlled supply of water to combat a potential Class A fire risk. Various types of reels are available to meet specific needs.

* Standard Hose Reel range also available in 50M
Product Code- WA5019P

	Standard Hose Reel	Stainless Steel Hose Reel	Swing Arm Hose Reel
Hose - Length x Diameter	36 m x 19 mm	36 m x 19 mm	36 m x 19 mm
Approvals	AS/NZS 1221	AS/NZS 1221	AS/NZS 1221
Minimum Inlet Pressure	220 kPa	220 kPa	220 kPa
Maximum Working Pressure	1,000 kPa	1,000 kPa	1,000 kPa
Drum	Polypropylene Copolymer	Polypropylene Copolymer	Polypropylene Copolymer
Drum Side Plates	Zinc Plated Mild Steel Powder Coated Red	304 Stainless Steel Powder Coated Red	Steel Sheet Powder Coated Red
Gland Assembly	Acetal Copolymer	Acetal Copolymer	Acetal Copolymer
Waterway Assembly	Galvanised Mild Steel	Galvanised Mild Steel	Galvanised Mild Steel
Ball Valve Assembly	Brass Body / Zinc Plated Mild Steel Handle	Brass Body / 304 Stainless Steel Handle	Brass Body / Mild Steel Handles
Nozzle Assembly	Brass	Brass	Brass
Hose Guide Assembly	304 Stainless Steel + NYLON6	304 Stainless Steel + NYLON6	Mild Steel, Zinc Plated
Mounting Shoe	Zinc Plated Mild Steel	304 Stainless Steel	Swing Arm. Swing Arm Kit available. Part Number: FHR3619P480KIT
Union	Galvanised Malleable Iron	304 Stainless Steel	Malleable Iron, Galvanised
Product Code	WA3619P	WA3619SS	WA3619P480