

# Water Extinguisher

Water fire extinguishers discharge a stream of water onto the fire, lowering the temperature of the burning material to below ignition point.

Water extinguishers are suitable for Class A fires.



|                        |                                    | 9.0 litre Water   |
|------------------------|------------------------------------|---|
| Agent Capacity         |                                    | 9.0 litres  |
| Agent Type             |                                    | Water   |
| Weight Full (approx)   |                                    | 12.5 kg   |
| Fire Rating            |                                    | 4A  |
| Approvals              |                                    | AS/NZS 1841.2   |
| Discharge Time         |                                    | 80 sec  |
| Effective Range        |                                    | 6 m   |
| Dimensions             | – Height<br>– Width<br>– Depth     | 592 mm<br>240mm<br>180 mm                               |
| Cylinder Pressure Test |                                    | 5 Yearly  |
| Periodic Test Pressure |                                    | 2 MPa   |
| Operating Pressure     |                                    | 620 kPa   |
| Construction           | – Cylinder<br>– Valve<br>– Handles | Stainless Steel<br>Brass<br>Stainless Steel             |
| Finish                 | – Cylinder<br>– Valve<br>– Handles | Painted Red<br>Nickel Plated<br>Vibration Shot Blasting |
| Product Code           |                                    | WA9.0H20  |
| FERN No.               |                                    | 4656.02-200   |