

# FREEDOL SF **3F**



## ✓ **Fluorine Free Foam FFF-AR 3x3 concentrate**

Class B fuels - Hydrocarbon and Polar Solvent  
fuels Class A fuels - Wood, paper and Tyres



## ✓ **Solvent Free**

50% reduction on COD and BOD at water treatment plants

## ✓ **Siloxane Free**

No long term persistent or toxic impact on water systems

## ✓ **Future proof**

No regulations to restrict future use

## ✓ **Advanced formulation**

Useable with fixed, portable and vehicle foam suppression systems

**UK manufacturing with a clear environmental vision**

# FREEDOL SF

# 3F

SF

## Synthetic Foam Concentrate FFF AR 3x3 Fluorine Free Solvent Free

### PERFORMANCE & WARRANTY

FREEGEN SF-LV meets international standards

EN 1568-1 & 2: Pass

EN 1568-3: Class 1-A

EN 1568-4: Class 1A (Acetone) - 1B (Isopropanol)

ICAO Level B

LASTFIRE

FREEGEN SF-LV can be used with tap and sea water.

FREEGEN SF-LV can be used with all known equipment on the market.

FREEGEN SF-LV has a 10 years warranty in its original packaging and at storage temperatures -30°C / +60°C.

### PHYSICAL DATA

Appearance /colour

Concentration of use on Hydrocarbons

Concentration of use on Solvents

Specific Gravity at 20°C (Kg/dm<sup>3</sup>)

Viscosity at 20°C (mPa.s)

Ph at 20°C

Freezing point

Sediments after ageing

Surface tension at 3% (mN/m)

### FOAM QUALITY AT 3%

Low Expansion

Drainage Time 25% / 50%

Medium expansion

High expansion

Foam Expansion values depend on the equipment

### FREEGEN SF-LV

off-white

3 %

3 %

1.05

1000

7,5

-8°C

0 %

25

7

> 30 min / > 60 min

80

400

