

SAFETY DATA SHEET

WORMALD ABE FIRE EXTINGUISHER

Infosafe No.: LQBOC
ISSUED Date : 28/04/2023
ISSUED by: WORMALD AUSTRALIA PTY LTD

Section 1 - Identification

Product Identifier

WORMALD ABE FIRE EXTINGUISHER

Company Name

WORMALD AUSTRALIA PTY LTD (ABN 80 008 399 004)

Address

91 Derby Street Silverwater
NSW 2128 Australia

Telephone/Fax Number

Tel: 133 166

Emergency Phone Number

133 166

Emergency Contact Name

John Lynch

E-mail Address

jlynch@wormald.com.au

Recommended use of the chemical and restrictions on use

Fire extinguishing agent

Section 2 - Hazard(s) Identification

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Gases under pressure: Category Compressed gas

Skin corrosion/irritation: Category 2

Eye damage/irritation: Category 2

Specific target organ toxicity (single exposure): Category 3 (Respiratory tract irritation)

Hazardous to the Aquatic Environment - Acute Hazard: Category 3

Hazardous to the Aquatic Environment - Long-Term Hazard: Category 4

Signal Word (s)

WARNING

Hazard Statement (s)

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H402 Harmful to aquatic life.

H413 May cause long lasting harmful effects to aquatic life.

Pictogram (s)

Gas cylinder, Exclamation mark



Precautionary Statement – Prevention

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash skin thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statement – Response

- P312 Call a POISON CENTER/doctor if you feel unwell.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary Statement – Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P410+P403 Protect from sunlight. Store in a well-ventilated place.

Precautionary Statement – Disposal

- P501 Dispose of contents/container to an approved waste disposal plant.

Section 3 - Composition and Information on Ingredients

Ingredients

Name	CAS	Proportion
Ammonium phosphate, monobasic	7722-76-1	40-90 %
Ammonium Sulfate	7783-20-2	10-60 %
Silica Gel	112926-00-8	0-<1 %
Nitrogen	7727-37-9	Propellant

Section 4 - First Aid Measures

Inhalation

Avoid becoming a casualty - to protect rescuer, use air-viva, oxy-viva or one-way mask. Remove affected person from contaminated area - Apply artificial respiration if not breathing. Do not give direct mouth to mouth resuscitation. Resuscitate in a well ventilated area. Seek IMMEDIATE medical attention. Note: in confined space - DO NOT ATTEMPT RESCUE WITHOUT ADEQUATE RESPIRATORY PROTECTION.

Ingestion

Not considered a potential route of exposure.

Skin

Remove all contaminated clothing immediately. Clothing frozen to the skin should be thawed before being removed. Wash affected area thoroughly with soap and water. For Frostbite: Flush affected areas with lukewarm water. Do not use hot water. Treat as thermal burns. Seek IMMEDIATE medical attention.

Eye

If eye tissue is frozen, seek IMMEDIATE medical attention. If tissue is not frozen, immediately irrigate with copious amounts of water for at least 15 minutes. Remove contact lenses. Eyelids to be held open. Seek medical attention.

First Aid Facilities

Eyewash, safety shower and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

Section 5 - Firefighting Measures

Suitable Extinguishing Media

Product is a fire extinguishing agent. Use extinguishing agent suitable for type of surrounding fire.

Hazards from Combustion Products

Non combustible material. Thermal decomposition may produce toxic and/or irritating fumes and gases including: nitrogen oxides (NO_x), phosphorus oxides (PO_x), sulfur oxides (SO_x) and silicon dioxide (SiO₂).

Specific hazards arising from the chemical

Contains gas under pressure; may explode if heated or may become a projectile in a fire. Fire exposed containers may vent contents through pressure relief devices. High concentrations of gas may cause asphyxiation without warning.

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapours or fumes. Water spray may be used to cool down heat-exposed containers. Fight fire from safe location.

Section 6 - Accidental Release Measures

Emergency Procedures

Remove all sources of ignition. Increase ventilation. Evacuate all unprotected personnel. Use self-contained breathing apparatus (S.C.B.A) and full protective clothing to minimise exposure. Allow gas to vent safely to atmosphere, preferably in well ventilated, remote location. Monitor oxygen concentration in confined spaces. Check for leaks using pressure drop test or soapy water on joints and outlets. Shut cylinder valve to stop leak if possible and safe to do so. Check gas concentration to ensure area is safe before removing protective equipment. Damaged gas cylinders should be returned to the supplier.

Section 7 - Handling and Storage

Precautions for Safe Handling

Use in a well ventilated area. Wear appropriate personal protective equipment and clothing to prevent exposure. Use smallest possible amounts in designated areas with adequate ventilation. Maintain high standards of personal hygiene ie. washing hands prior to eating, drinking, smoking or using toilet facilities. DO NOT enter confined spaces where gas may have collected. Suck back of water into the container must be prevented. Do not allow back feed into the container. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Refer to supplier's container handling instructions.

Conditions for safe storage, including any incompatibilities

Protect containers against physical damage. Store in a cool, dry, well-ventilated place, low fire risk area. Protect from extremes of temperature and weather. Do not allow any part of a cylinder to be exposed above 45°C. Storage areas should be kept clean and free from flammable materials. Ensure that containers are properly vented to prevent build up of pressure. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS 4332 - The storage and handling of gases in cylinders.

Storage Temperatures

Below 45°C

Unsuitable Materials

Avoid strong acids and bases.

Section 8 - Exposure Controls and Personal Protection

Occupational exposure limit values

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Precipitated silica/silica gel

TWA: 10 mg/m³

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

Source: Safe Work Australia

Biological Monitoring

No biological limits allocated.

Control Banding

Not available

Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn.

Before entering a confined space where nitrogen is present, check to make sure sufficient Oxygen (19.5%) exists. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 2865 Australian Standard Safe working in a confined space, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye and Face Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material such as PVC. Final choice of appropriate gloves will vary according to individual circumstances. i. e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Thermal Hazards

No further relevant information available.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

Other Information

Nitrogen is an asphyxiant gas which when present in an atmosphere in high concentration, lead to reduction of oxygen concentration by displacement or dilution. It is not appropriate to recommend an exposure standard for each simple asphyxiant, rather it should be required that a sufficient oxygen concentration be maintained.

Section 9 - Physical and Chemical Properties

Properties	Description	Properties	Description
Form	Gas	Appearance	Compressed gas with white powder
Colour	White powder	Odour	Not available
Melting Point	Not available	Boiling Point	Not available
Decomposition Temperature	Not available	Solubility in Water	Miscible
Specific Gravity	Not available	pH	4.5
Vapour Pressure	Not available	Relative Vapour Density (Air=1)	Not available
Evaporation Rate	Not available	Odour Threshold	Not available
Viscosity	Not available	Volatile Component	Not available
Partition Coefficient: n-octanol/water (log value)	Not available	Density	Not available
Flash Point	Not available	Flammability	Not flammable
Auto-Ignition Temperature	Not available	Flammable Limits - Lower	Not available
Flammable Limits - Upper	Not available	Explosion Properties	Contains gas under pressure; may explode if heated.
Oxidising Properties	Not available	Particle Characteristics	Not applicable

Section 10 - Stability and Reactivity

Reactivity

Reacts with incompatible materials.

Chemical Stability

Stable under normal conditions of storage and handling.

Possibility of hazardous reactions

Reacts with incompatible materials.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

Avoid strong acids and bases.

Hazardous Decomposition Products

Thermal decomposition may produce toxic and/or irritating fumes and gases including: nitrogen oxides (NO_x), phosphorus oxides (PO_x), sulfur oxides (SO_x) and silicon dioxide (SiO₂).

Hazardous Polymerization

Will not occur.

Section 11 - Toxicological Information

Toxicology Information

No toxicity data available for this material. The available acute toxicity data for the ingredients are given below.

Acute Toxicity - Oral

Ammonium phosphate, monobasic

LD50 (Rat): >2000 mg/kg

Ammonium sulfate
LD50 (Rat): 2840 mg/kg

Silica gel
LD50 (Rat): >4500 mg/kg

Acute Toxicity - Dermal

Ammonium phosphate, monobasic
LD50 (Rat): >5000 mg/kg

Ammonium sulfate
LD50 (Rat): >2000 mg/kg

Silica gel
LD50 (Rat): >2000 mg/kg

Acute Toxicity - Inhalation

Ammonium phosphate, monobasic
LC50 (Rat): >5 mg/l/4h

Silica gel
LC50 (Rat): >0.09<0.84 mg/l/4h

Ingestion

Ingestion unlikely due to form of product.

Inhalation

May cause respiratory irritation. Inhalation of product vapours/dust can cause irritation of the nose, throat and respiratory system. Nitrogen is an asphyxiant gas which when present in an atmosphere in high concentration, lead to reduction of oxygen concentration by displacement or dilution. It is not appropriate to recommend an exposure standard for each simple asphyxiant, rather it should be required that a sufficient oxygen concentration be maintained.

Skin

Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

May cause frostbite injuries to skin due to uncontrolled release of compressed gas resulting in redness, tissue destruction.

Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

May cause frostbite injuries to eyes due to uncontrolled release of compressed gas resulting in stinging, tearing, blurred vision and possibly permanent damage to eyes.

Serious Eye Damage/Irritation

Silica gel
Eye (Rabbit): 8.3 mg/48hr [RTECS]

Respiratory Sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ Cell Mutagenicity

Not considered to be a mutagenic hazard.

Carcinogenicity

Not considered to be a carcinogenic hazard.

Silica, amorphous is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

Reproductive Toxicity

Not considered to be toxic to reproduction.

STOT - Single Exposure

May cause respiratory irritation.

STOT - Repeated Exposure

Not expected to cause toxicity to a specific target organ.

Aspiration Hazard

Not expected to be an aspiration hazard.

Other Information

This material contains asphyxiant gas, which when present in an atmosphere in high concentrations, lead to a reduction of oxygen concentration by displacement or dilution. It is not appropriate to recommend an exposure standard for each simple asphyxiant, rather it should be required that a sufficient oxygen concentration be maintained. The minimum oxygen content in air should be 19.5 per cent by volume under normal atmospheric pressure. Unconsciousness and death can rapidly ensue in an environment, which is deficient in oxygen.

Section 12 - Ecological Information

Ecotoxicity

Harmful to aquatic life. May cause long lasting harmful effects to aquatic life.

No ecological data available for this material. The available ecological data for the ingredients is given below:

Persistence and degradability

Ammonium phosphate, monobasic

Persistence Water/Soil: HIGH

Persistence Air: HIGH

Ammonium sulfate

Persistence Water/Soil: HIGH

Persistence Air: HIGH

Silica gel

Persistence Water/Soil: LOW

Persistence Air: LOW

Mobility

Ammonium phosphate, monobasic

Mobility in soil: LOW (KOC = 1)

Ammonium sulfate

Mobility in soil: LOW (KOC = 6.124)

Silica gel

Mobility in soil: LOW (KOC = 23.74)

Bioaccumulative Potential

Ammonium phosphate, monobasic

Bioaccumulation: LOW (LogKOW = -0.7699)

Ammonium sulfate

Bioaccumulation: LOW (LogKOW = -2.2002)

Silica gel

Bioaccumulation: LOW (LogKOW = 0.5294)

Other Adverse Effects

Not available

Environmental Protection

Prevent this material entering waterways, drains and sewers.

Acute Toxicity - Fish

Ammonium phosphate, monobasic

NOEC(ECx) (Fish): 100 mg/l/96h

LC50 (Fish): >100mg/l/96h

Ammonium sulfate

LC50 (Fish): 0.29-0.53 mg/l/96h

Silica gel

LC50 (Fish): 1033.016mg/l/96h

Acute Toxicity - Algae

Ammonium phosphate, monobasic

EC50 (Algae or other aquatic plants): >100 mg/l/72h

Silica gel

EC50 (Algae or other aquatic plants): 217.576 mg/l/96h

EC50 (Algae or other aquatic plants): 14.1mg/l/72h

Acute Toxicity - Other Organisms

Ammonium phosphate, monobasic

EC50 (Crustacea): >100 mg/l/48h

Ammonium sulfate

EC50 (Crustacea): 52-67 mg/l/48h

Silica gel

EC50 (Crustacea): >86 mg/l/48h

EC50 (Crustacea): >=10000mg/l/24h

Chronic Toxicity - Fish

Ammonium sulfate

NOEC(ECx) (fish): 0.064mg/l/216h

Hazardous to the Ozone Layer

This product is not expected to deplete the ozone layer.

Section 13 - Disposal Considerations

Disposal Considerations

Dispose of waste according to applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations.

To minimise personal exposure to the chemical, refer to Section 8 — Exposure controls and personal protection.

Section 14 - Transport Information

Transport Information

Road and Rail Transport (ADG Code):

This material is classified as Dangerous Goods Division 2.2 Non-flammable Non-toxic Gases.

Dangerous Goods are incompatible in a placard load with any of the following:

- Class 1: Explosives
- Division 2.1 Flammable Gas when the Division 2.2 gas has a subsidiary risk 5.1 except when all are packed in cylinders or pressure drums not exceeding 500L capacity.
- Division 2.3 Toxic Gas when the Division 2.2 gas has a subsidiary risk 5.1 except when all are packed in cylinders or pressure drums not exceeding 500L capacity.
- Division 4.2: Spontaneously combustible substances
- Division 5.2: Organic peroxides

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Division: 2.2

UN-No: 1044

Proper Shipping Name: FIRE EXTINGUISHERS with compressed or liquefied gas

EmS: F-C,S-V

Special Provisions: 225

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Division: 2.2

UN-No: 1044

Proper Shipping Name: Fire extinguishers with compressed or liquefied gas

Packaging Instructions (cargo only): 213

Packaging Instructions (passenger & cargo): 213

Hazard label: Non-flammable gas

Special Provisions: A19

ADG U.N. Number

1044

ADG Proper Shipping Name

FIRE EXTINGUISHERS with compressed or liquefied gas

ADG Transport Hazard Class

2.2

IERG Number

08

Special Precautions for User

Not available

IMDG Marine pollutant

No

Transport in Bulk

Not available

Section 15 - Regulatory Information

Regulatory Information

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) including Work, Health and Safety Regulations, Australia.

Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Poisons Schedule

Not Scheduled

Montreal Protocol

Not listed

Stockholm Convention

Not listed

Rotterdam Convention

Not listed

International Convention for the Prevention of Pollution from Ships (MARPOL)

Not listed

Agricultural and Veterinary Chemicals Act 1994

Not listed

Basel Convention

Not listed

Section 16 - Any Other Relevant Information

Date of Preparation

SDS Created: April 2023

Version Number

1.0

Literature References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Code of Practice for Supply Diversion into Illicit Drug Manufacture.

National Code of Practice for Chemicals of Security Concern.

Agricultural Compounds and Veterinary Chemicals Act.

International Agency for Research on Cancer (IARC) Monographs.

Montreal Protocol on Substances that Deplete the Ozone Layer.

Stockholm Convention on Persistent Organic Pollutants (POPs).

Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade.

Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and Their Disposal.

International Air Transport Association (IATA) Dangerous Goods Regulations.

International Maritime Dangerous Goods (IMDG) Code.

Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

Globally Harmonised System of Classification and Labelling of Chemicals.(7th revised edition).

Code of Practice: Managing Noise and Preventing Hearing Loss at Work.

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.